

APPLICATIONS

The Vandalex® Medium made for PL lamps or Incandescent is a quality vandal proof luminaire engineered with high efficiency, broad beam patterns and excellent visual uniformity. Designed for high abuse areas such as Correctional Facilities, Parking Garages, Recreational Areas, Public Buildings, Schools, Hotels, Hospitals and Shopping Malls.



SPECIFICATIONS

HOUSING: Die formed of 16 ga. steel, rigidly fabricated, to insure true and perfect alignment.

REFLECTOR/COMPONENT PLATE: Die formed of code gauge steel and mounted securely to fixture housing.

ELECTRICAL: Incandescent sockets of glazed porcelain with nickel plated interior for one 75W A19 lamp. Fluorescent ballast, 7 watt PL, Twin-Tube (G23 socket) or 9 watt PL Quad Lamp (G23-2 socket), 13 watt PL Quad Lamp (GX23-2 socket), minimum starting temperature is 7 watt/0°F, 9 watt/+25°F, 13 watt/+32°F. NPF thermally protected class "P", approved for 118 volt 60 Hz. operation. Other voltages available. (CONSULT FACTORY).




MOUNTING: Ceiling or wall mounting for indoor or outdoor areas.

DIFFUSER/SECURITY: Injection molded, clear prismatic .125" Lexan® polycarbonate. Integral molded structural supports for maximum structural strength and ultraviolet inhibitors to minimize discoloring. Fully neoprene gasketed for moisture and dustproof. Tamperproof stainless steel screws (Torx, center pin type) and integral locking lugs opposite the retention screws.

FINISH: All steel component parts are completely protected against rust and discoloration by an Anchored Process and coated with a five stage powder coated Dura White finish for maximum durability, providing a high reflectance efficiency.

CERTIFICATION: The VANDALEX® MINI is U.L. and C.U.L. listed for Damp Location ("DL") and Wet Location ("WL") for ceiling applications only, and bears the label of the I.B.E.W./AFL-CIO, Local #3.

VANDALEX® and LEGION® are registered trademarks of LEGION LIGHTING CO., INC. LEXAN® is a trademark of General Electric.



TOP

ORDERING DATA

Cat. No.	No. and Type Lamps	Socket Base	Wt.
"PL" FLUORESCENT			
1888-2F9TT-UBP	2-9W/6T4/Twin	G23	4
1888-2F9Q-UBP	2-9W/4T4/Quad	G23-2	4
1888-2F13Q-UBP	2-13W/5T4/Quad	GX23-2	4
INCANDESCENT			
1888-175IN-UBP	1-75W-A19	Medium	3

OPTIONS

Suffix "BBS" for 1/2" Conduit Steel Adapter (Bronze Finish).
 Suffix "WH" for White Diffuser.
 Suffix "DL" for Damp Location.
 Suffix "WL" for Wet Location (Ceiling mount only).

ACCESSORIES

TPSDT – Tamperproof Torx screwdriver


PHOTOMETRICS

Multipliers for Different Mounting Heights

Mounting Height	9'	10'	12'	14'
Multiply by	.9	.8	.7	.6

Multipliers for Different Wattages

Wattage	Incand.	PL	
	7	9	13
Multiply by	.3	.5	.7



Multiples of mounting height
 75W incandescent @ 8' mounting height

